

Cellulose Casing

Usage:

Cellulose casing, also called “skinless casing”, is made from natural fiber. It is engaged with the characteristics of high strength and good elasticity. It can maintain a good size and appearance of the sausage, and has an excellent smoking performance. Cellulose casing has become an indispensable raw material for sausage production like hot dogs and frankfurt sausage.



Product Range:

Vicel casing variety: Clear casing, Stripe casing, Color casing.

Caliber: US 16 to 36, Stick length: 55 to 125 feet.

The most popular stripe products are black stripe, blue stripe and red stripe.

Color casings mainly include orange, smoke and smoke with red stripe.

Fully meet the requirement of different sausages and customization.

Advantage:

- ➔ Uniform caliber, stable size.
- ➔ No refrigeration, no soak, directly use.
- ➔ High strength, high abrasive resistance, suitable for high speed.
- ➔ Superior permeability performance, and smoking performance.
- ➔ Various types of enclosure, to meet different needs.



Storage:

Stand vertically and downward the open end; Seal to prevent moisture loss and pollution.

Store away from exposure and pollution, temperature ≤ 25 °C and RH: 40% to 70%.

For processing of meat products:

Ham

Hot Dogs

Roast Sausage

Red Sausage

Vienna Sausage

Italian Intestine

Frankfurt

Crispy Intestine

Germany Bifi

Salami Sausage

欧径 EU	美径 US	建议灌装直径 (mm)	填料管	标准棒长					
			mm	9 in	11 in	12 in	14 in	15.5 in	20 in
13	15	14.5-15.2	8	55'	70'	84'	95'	110-125'	
14	16	15.3-16.1	9	55'	70'	84'	95'	110-125'	
15	17	16.2-17.0	9	55'	70'	84'	95'	110-125'	
16	18	17.1-17.9	10	55'	70'	84'	95'	110-125'	
17	19	18.0-18.8	10	55'	70'	84'	95'	110-125'	
18	20	18.9-19.6	10	55'	70'	84'	95'	110-125'	140'
19	21	19.7-20.6	11	55'	70'	84'	95'	110-125'	140-160'
20	22	20.7-21.6	12	55'	70'	84'	95'	110-125'	140-160'
21	23	21.7-22.6	12	55'	70'	84'	95'	110-125'	140-160'
22	24	22.7-23.6	13	55'	70'	84'	95'	110-125'	140-160'
23	25	23.7-24.6	13	55'	70'	84'	95'	110-125'	140-160'
24	26	24.7-25.6	14	55'	70'	84'	95'	110-125'	140-160'
25	27	25.7-26.6	14	55'	70'	84'	95'	110-125'	140-160'
26	28	26.7-27.6	15	55'	70'	84'	95'	110-125'	140-160'
27	29	27.7-28.6	15	55'	70'	84'	95'	110-125'	
28	30	28.7-29.6	16	55'	70'	84'	95'	110-125'	
29	31	29.7-30.6	16	55'	70'	84'	95'		
30	32	30.7-31.6	17	55'	70'	84'			
31	33	31.7-32.6	17	55'	70'	84'			
32	34	32.7-33.6	18	55'	70'	84'			
33	35	33.7-34.6	18	55'	70'	84'			
34	36	34.7-35.6	18	55'	70'	84'			
Standard Caddy		16 US – 26 US		27 US – 34 US			35 US – 36 US		
55 and 70 feet		400 sticks / carton		300 sticks / carton			200 sticks / carton		
84 and 95 feet		300 sticks / carton		200 sticks / carton			200 sticks / carton		
100 feet and greater		200 sticks / carton		200 sticks / carton			200 sticks / carton		

Conditions of Use:

1. Always ensure the stuffing machine is set up correctly.
2. Typically the casing is processed at relative humidity no less than 40%;
The stuffed casing surface should be moist when smoke is applied.
3. Before peeling, the stuffed casing must be chilled quickly, preferably with brine chill if available.
4. The stuffed casing should be extremely damp in order to peel with temperature less than 4 °C.

